



SWE335F



◆ High-end and luxury

F-series new coating, the whole machine is grand and magnificent, beautiful and powerful; Isuzu GH-6HK1 engine, top power configuration, large displacement reserve hydraulic system, easy to control under heavy load working conditions; Brand-new cab with large field of vision, equipped with 8-inch high-definition LCD screen, easy for operation and maintenance; Rear view camera, 360° without dead angles; Super large toolbox for your convenience.

◆ Durable

The bearing capacity of the taller and longer chassis system can reach 36t, securing the construction and operation under harsh conditions; the structural parts of the working device are designed in line with the mine-type configuration of large excavators, which is unstoppable.

◆ Efficiency doubling

Independent innovation control technology, convenient and efficient; Equipped with 1.7m³ large capacity hyperbolic reinforced bucket, with high efficiency.

◆ Multifunctional

The support of crushing system is provided, which is convenient for customers to install crushing hammer.

ENGINE		UNIT	SWE335F
Working weight		kg	32800
Capacity of bucket		m ³	1.6~1.7
Engine	Brand		ISUZU
	Type		GH-6HK1
	Rated output power	kW/rpm	212/2000
Dimension parameters	A Transportation length	mm	10545
	B Transportation height	mm	3490
	C Total width	mm	3190
	D Counterweight ground clearance	mm	1235
	E Min. ground clearance	mm	530
	F Tail slewing radius	mm	3250
	G Ground contact length of track	mm	3930
	H Track length	mm	4860
	I Track gauge	mm	2590
	J Track width	mm	3190
	K Creeper tread width	mm	600
	L Cab height	mm	3230
	M Hood height	mm	2690
	N Turntable width	mm	3110
Scope of work	a Maximum excavation height	mm	10350
	b Maximum dumping height	mm	7300
	c Maximum digging depth	mm	7000
	d Digging depth (2.44 mhorizontally)	mm	6860
	e Maximum vertical digging depth	mm	5900
	f Maximum digging distance	mm	10525
	g Maximum digging distance on ground	mm	10320
	h Minimum front slewing radius	mm	3955
Swing arm length		mm	6150
Bucket arm length		mm	2900
Bucket arm digging force		kN	170
Bucket digging force		kN	220
Speed (high/low)		km/h	5.8/3.6
Slewing speed		rpm	11.42
Fuel tank capacity		L	520
Hydraulic fuel tank capacity		L	400

